

CABRILLO SERIES CORE 2.0mm 12 mil WL GLUE DOWN LVT


SPECIFICATIONS

Construction:	Solid Luxury Vinyl Tile Consisting Of A Wear Layer, Printed Film, And 2.0mm Solid Core	
Installation Method:	Glue Down	
Plank Size:	7"x48"	
Total Thickness:	2.0mm	
Wear Layer:	12 mil	
Finish:	Polyurethane Top Coating	
Texture:	Deep Embossing	
Sq Ft Per Carton:	51.34 Sq Ft	
Pieces Per Carton:	22	
Cartons Per Pallet:	55	
Composition:	Phthalate-Free Polyvinyl Chloride	


TESTING

Product Classification:	ASTM F1700	Class III, Type B, Embossed Surface Meets And Exceeds Passing Requirements
Radiant Panel:	ASTM E648	Meets And Exceeds Passing Requirements (Class 1)
Slip Coefficient:	ASTM D2047	Meets And Exceeds Passing Requirements
Resistance To Chemical:	ASTM F925	Meets And Exceeds Passing Requirements
Impact Acoustical:	ASTM E492	Exceeds Code Requirement of 54 IIC over 6" Concrete With A Rating Of 70 db
Static Load Limit:	ASTM F970	Meets And Exceeds Passing Requirements
Quality Management:	ISO 9001	Meets And Exceeds Passing Requirements
Environmental Management:	ISO 14001	Meets And Exceeds Passing Requirements


INSTALLATION




Herringbone



Double
Herringbone



Staggered



Basket
Weave

INSTRUCTIONS



PRODUCT WARRANTY

Limited Warranty:
Lifetime Residential, 10 Year Light Commercial



GENERAL INFORMATION

For Pricing, Samples, Warranties and Installation Guides, please contact us at contact@catalinaproducts.international or call 714-716-1667.