

# CABRILLO SERIES 5.5mm CLICK LVT



CATALINA  
PRODUCTS  
INTERNATIONAL

714.716.1667 | contact@catalinaproducts.international

## SPECIFICATIONS

Sizes (inches)	9x48
Thickness	5.5mm
Attachment/Backing	1.5mm EVA

## TESTING

Characteristic	Test Specification	Results
Squareness	ASTM F2055	0.010 in. max
Size and Tolerance	ASTM F2055	+0.016 in per linear foot
Thickness	ASTM F386	Nominal +0.005 in.
Flexibility	ASTM F137	≤1.0 in., no cracks or breaks
Dimensional Stability	ASTM F2199	≤0.024 in. per linear foot
Heavy Metal Presence/Absence	EN 71-3 C	Meets spec
Smoke Generation Resistance	EN ISO 9239-1	Results 9.1
Smoke Generation Resistance Non-Flaming Mode	EN ISO	Passes
Flammability	ASTM E648	Class 1 rating
Residual Indentation	ASTM F1914	Average less than 8%
Static Load Limit	ASTM-F-970	1000psi
Requirements for Wear Group	prEN 660-1 prEN 660-2	Thickness loss 0.30<1<0.60 Volume loss 7.5<F<15.0
Slip Resistance	ASTM D2047	>0.6 wet, >0.6 dry
Resistance to Light	ASTM F1515	ΔE ≤ 8
Resistance to Heat	ASTM F1514	ΔE ≤ 8
Electrical Behavior (ESD)	EN 1815: 1997 2	0 kV when tested at 23 C+1 C
Underfloor Heating		Suitable for installing over floor heating
Curling After Exposure to Heat	EN 434	< 2mm
Recycled Vinyl Content		Approximately 40%
Recyclability		Can be recycled

## PRODUCT WARRANTY

10-Year limited commercial

## FLOORSCORE CERTIFIED



## GENERAL INFORMATION

For Pricing, Samples, Warranties and Installation Guides, please contact us at contact@catalinaproducts.international or call 714-716-1667.