

CABRILLO SERIES
6.5mm COMMERCIAL CLICK LVT

SPECIFICATIONS

Thickness	6.5mm
Wear Layer	20 mil
Abrasion Class	AC5 / Class 33: Heavy Traffic

CERTIFICATION & CLASSIFICATION

Type of Floor Covering	Resilient flooring in modular format with rigid core (SPC)
CE Certification	Yes
Classification	Heavy Traffic: Class 33

TECHNICAL CHARACTERISTICS

Total Thickness	6.5mm
Wear Layer Thickness	20 mil WL 0.50mm
Surface Treatment	PUR
Total Weight	2.17 lbs/sqft. = 10.40 kg/m ²
Wear Layer Binder Content	Type I
Form of Delivery	9" x 60" = 18.75 sqft. 5 Pieces per box

TECHNICAL PERFORMANCE

Dimensional Stability	≤ 0.10%
Reaction to Fire	Bfl-S1 PASS
Residual Identification	Required Value: ≤ 0.10mm Average Measured Value: 0.03mm
Furniture Leg	No Damage
Castor Chair	No Damage
Curl Resultant to Heat	≤ 2mm PASS
Smoke Resistance	PASS
Impact Sound Reduction	w = 11 Db
Light Fastness	PASS
Resistance to Chemicals	Good Resistance PASS
Slip Resistance	R9 Pass
Static Load	PASS

GENERAL INFORMATION

For Pricing, Samples, Warranties and Installation Guides, please contact us at contact@catalinaproducts.international or call 714-716-1667.

FLOORSCORE CERTIFIED

