

# NURAZZO STONE TILE



CATALINA  
PRODUCTS  
INTERNATIONAL

714.716.1667 | contact@catalinaproducts.international

## SPECIFICATIONS

Gauge	1/4"
Size:	24"x24"



## COLOR

SS012 Snow	SS063 Deep Sea
SS051 Almond	SS039 Fire
SS065 Stone	SS021 Onyx

## TECHNICAL DATA

Abrasive Resistance	ASTM D-4060	35 mg
Impact Resistance	MILD3134F	Withstands 16ft/lbs w/o cracking, delamination or chipping
Slip Resistance	ASTMD-2047	
Wet		.62
Dry		.85
Compressive Strength	ASTM C-597, 7 days	10,000 psi minimum
Tensile Strength	ASTM C-307	2,500 psi
Flame Spread	ASTM D-84	20
Smoke Generation	ASTM E-622	
Flaming		124
Non-Flaming		20
Fire Rating		Class A
Water Absorption	ASTM D-570	0.01%
Freeze Thaw	ASTM 6-1026	No Effect
Stain Resistance	ASTMD-2299	Completely removed after 24 hours
Toxicity Material Safety		Negative
Critical Radiant Flux	ASTM D-648	1.0 (Class 1)
Fungus and Bacteria Growth	MIL-F-5205	Will not support growth of fungus or bacteria when subject to mildew and bacteria tests
Indentation	MIL-D3134F	Withstands 2,000lbs/sq in for 30 minutes without indentation
Flexural Strength	ASTM C-580	3,000 psi
Thermal Coefficient of Expansions	ASTM-531	21x10 <sup>6</sup>

## GENERAL INFORMATION

Nurazzo is manufactured from marble and glass chips embedded in an epoxy resin and then polished to a high-resolution finish. Nurazzo Tile can contain up to 70% post consumer recycled contents. Prior to installation, Nurazzo tile should be stored in a controlled environment inside the building for 72 hours at a minimum temperature of 70 degrees F. Pallets of tile should be broken down, removed from packaging and tile stacked to facilitate the warming process. Keep all traffic off the completed floor for 24 hours.

For Pricing, Samples, Warranties and Installation Guides, please contact us at [contact@catalinaproducts.international](mailto:contact@catalinaproducts.international) or call 714-716-1667