

POST-INSTALLATION MAINTENANCE

- Keep traffic to a minimum during the first 24 hours to allow the adhesive to fully cure.
- Light foot traffic is fine after 24 hours.
- Regular traffic can be resumed after 48 hours.
- Keep furniture off the floor for 24 hours so the adhesive has adequate time to cure.
- Always protect the floor when moving heavy furniture and appliances because you don't want to gouge or tear the floor.
- Wait for a minimum of 7 days following installation before any wet-wash, or scrubbing the floor.
- Clean with a neutral pH cleaner, utilizing a red or white cleaning pad, following the cleaner manufacturer's guidelines for dilution and usage ratios.
- Use the minimum amount of water on the floor to facilitate the efficacy of the cleaner.
- Rinse well with clean water and remove all excess water.
- Use of an auto-scrubber is optimal because it immediately vacuums up residual water.
- No need for stripping or waxing.
- Like any very high-quality resilient flooring material, CPI flooring products can become slippery when wet. Allow time for the floor to dry after cleaning.
- Keep the room temperature between 65° - 85°F for at least 48 hours after installation.

REGULAR CARE

- Maintain room temperature between 55° - 85°F.
- Use blinds or curtains during peak sunlight hours.
- Prolonged exposure from direct sunlight may cause volatile temperature variations, which may discolor or damage your floor.
- Always protect the floor when moving heavy objects to prevent permanent scratches or tears.
- Use appropriately wide floor protectors under each leg of tables, chairs, and any heavy furnishing to avoid permanent damage.
- Place walk—off mats at all exterior entrances they help protect the floor from outdoor intrusion from water, grease, sand, and asphalt residue from outdoor blacktop.
- DO NOT use rubber-based mats on the new HVT floors.
- Use solvent cleaners and clean as required with a neutral pH cleaner, utilizing a red or white cleaning pad, following the cleaner manufacturer's guidelines for dilution and usage ratios.

- Use the minimum amount of water on the floor to facilitate the efficacy of the cleaner.
- Rinse well with clean water and remove all excess water.
- Use of an auto-scrubber is optimal because it immediately vacuums up residual water.
- No need for stripping or waxing.
- Avoid one-step "mop and polish" products, dishwashing liquids and oil-based cleaners.
- These may leave a residue which can attract dirt and dull the floor finish.
- Avoid cleaners that contain abrasives or solvents which may permanently damage the floor.
- All stain-forming and aggressive substances must be immediately removed from the surface.